

# Nstat ESD Control

## Clear Anti Static Tape with ESD Symbols

This clear Anti Static Tape with PRINTED ESD SYMBOLS, is ideal for general packaging applications at the static free work areas. The tape has the wording " Anti Static Tape " and both the Reaching Hand & the Three-Arrow symbols printed in black color. This product is designed to meet the static decay rate of MIL-B-81705C, and is available in 72 Yards (66 Meters) long & on 3" Paper or Plastic Cores.

### Specifications

Adhesion to Steel: 40 oz./inch

Tensile Strength: 25 lb./inch

Elongation: 20%

Backing: Cellulose film

Adhesive: Rubber-Based, Non-Staining

Thickness: 2.4 mils

Application Temperature: 50-130 F (10-55 C)

Surface Resistivity: 9.8 x 10e9 Ohms/Square

Decay Time: 0.12 Seconds

Part Numbers	Description	Length	Size
NS-T-51-S-1/2	Clear w/Symbols	72 Yards	1/2"
NS-T-51-S-3/4	Clear w/Symbols	72 Yards	3/4"
NS-T-51-S-1	Clear w/Symbols	72 Yards	1"
NS-T-51-S-2	Clear w/Symbols	72 Yards	2"

Call office for more sizes.



## P R O D U C T D A T A S H E E T

### Clear Anti Static Tape with ESD Symbols

**PRODUCT**

Clear Anti Static Tape

**ITEM NUMBER**

SEE ABOVE



Nstat ESD Control

USA and Canada: 1-866-516-7828  
Toll Free Mexico: 00180 05140052  
1004 Des Fabricants  
Terrebonne, QC, J6Y 2A6  
email: info@nstatesd.com  
www.NSTATESD.com