

Nstat ESD Control

Ground Cords

Nstat ground cords provide a reliable efficient method for grounding table mats, floor mats, wrist straps and benches. The common ground cords provide a common ground point required by ESD S6.1 & ANSI/ESD S20.20.

NS-53-CPG

Common Ground Cord

This common ground point cord connects two wrist straps and a work surface to ground, assuring that all parts are at the same ground potential. Easy to install. Simply snap it to a mat or work surface. Plug in the wrist strap coil cord, and connect the ring terminal to ground.



- * Provides the common ground point required in EIA 625, ESDA S6 and ANSI/ESD-S20.20.
- * Tough vinyl cord and strain relief provide a long service life.
- * Long, 15 foot cord.
- * 3/8" (10mm) stud (male) for mat connection.
- * #10 ring terminal for ground connection.

NS-1500R

Low Profile Ground Cord

With a low profile top, this common point ground cord connects two wrist straps and a work surface to ground, assuring that all parts are at the same ground potential. Easy to install. Two #19 screws allowing unit to be securely installed to workbench.



- * Provides the common ground point required in EIA 625, ESDA S6 and ANSI/ESD 20.20
- * Tough vinyl cord and strain relief provide a long service life.
- * Long, 15 foot cord.
- * Two #19 screws allowing unit to be securely installed to workbench.
- * 1 Meg Ohm resistor.

NS-2320-008-FMG

Mat Ground Cord

Perfect for grounding floor mats, runners and table mats. This 15 foot ground cord makes reaching ground easy. Easy to install. Simply snap it to a mat and connect the ring terminal to ground. The beveled cap prevents the snap from being removed by a chair or a cart. Cord is terminated with a ring terminal.



- * Tough vinyl cord and strain relief provide a long service life.
- * Long, 15 foot cord.
- * 3/8" (10mm) stud (male) for mat connection.
- * #10 ring terminal for ground connection.

Item Numbers:

NS-53-CPG
NS-1500R
NS-2320-008-FMG

Specifications:

Length:	15 Feet.
Snap:	3/8" (10mm)
Ground Connection:	#10 ring terminal.
Insulation:	PU/PVC Wire: 18 AWG 65 Strand high flex.
Resistor:	1 Meg Ohm mat to ground.
Color:	Black.

P R O D U C T D A T A S H E E T

Ground Cords

PRODUCT

Ground Cords

ITEM NUMBER

SEE ABOVE



Nstat ESD Control

USA and Canada: 1-866-516-7828
Toll Free Mexico: 00180 05140052
1004 Des Fabricants
Terrebonne, QC, J6Y 2A6
email: info@nstatesd.com
www.NSTATESD.com