

Nstat ESD Control

Static Dissipative Rubber Bands

Antistatic rubber bands assure quick safe handling of ESD sensitive parts, tubes, totes and carriers. Rubber band length sizes are determined by laying the rubber band flat in the unstretched position.

Standards

Meets the requirements of ESD Standard DOD STD 263.

Specifications

ASTM TEST RESULTS TEST SERIES D991-85.

Temperature: 72 Degrees.

Humidity: 50%

Specimen: 0.4" Wide x 2.8 Long.

Band Color: White/Pink/Blue.

Current: 3mA

Voltage: 300 Volts.

Volume Resistivity: <0.1 M/Ohms - Cm.

Test Instruments: Monroe Stat-Arc 11 Model 265, H.V. Generator Sorenson 1030.20, Beckman Oscilloscope.

STATIC CONTROL TEST STANDARDS DOD STD 263.

Result Range:

- * Less than 0.5 Sec to 1% of test voltage surface.
- * Resistivity Range 50 to 100 M/Ohms.

Part Numbers

- NS-070008-01 (0.25" x 4.00", 1 Pound Bag)
- NS-070008-02 (0.25" x 4.00", 2 Pound Bag)
- NS-070008-03 (0.25" x 4.00", 3 Pound Bag)
- NS-070008-04 (0.25" x 4.00", 4 Pound Bag)
- NS-070008-05 (0.25" x 4.00", 5 Pound Bag)
- NS-070008-06 (0.25" x 4.00", 6 Pound Bag)
- NS-070008-10 (0.25" x 4.00", 10 Pound Bag)
- NS-070008-15 (0.25" x 4.00", 15 Pound Bag)
- NS-070008-20 (0.25" x 4.00", 20 Pound Bag)

* 1 pound = 155 elastics.



P R O D U C T D A T A S H E E T

Static Dissipative Rubber Bands

PRODUCT

ESD Rubber Bands

ITEM NUMBER

SEE ABOVE



Nstat ESD Control

USA and Canada: 1-866-516-7828
Toll Free Mexico: 00180 05140052
1004 Des Fabricants
Terrebonne, QC, J6Y 2A6
email: info@nstatesd.com
www.NSTATESD.com